



801 Industrial Park Dr.
Greenville, MI 48838
1.800.901.2395

AVAILABLE STOCK PROFILES 2019

Profile Series/Die#	Width	Alloy/ Temper	Overall Height	Fin Height	Base Height	Weight/Ft Weight/In	Approx C/W/3"	Outer Perimeter
A - #22665	5.375	6063-T5	1.375	1.000	0.375	4.420/.37	1.15	51.587
B - #24017	5.886	6063-T6	1.270	1.000	0.270	2.948/.25	1.75	39.594
C - #23841	7.280	6063-T6	1.300	1.000	0.300	4.406/.37	1.30	51.491
D - #23589	8.460	6063-T6	1.300	1.000	0.300	5.117/.43	1.10	59.581
E - #23909	10.080	6063-T6	2.875	2.500	0.375	11.912/.99	0.80	137.749
F - #24196	4.230	6063-T5	1.050	0.750	0.300	2.291/.19	2.15	24.611
G - #24300	10.000	6063-T6	1.300	1.000	0.300	5.958/.50	0.90	68.021
H - #24480	1.813	6063-T5	1.250	0.950	0.300	1.165/.10	4.50	15.153
I - #24601	3.500	6063-T5	1.050	0.750	0.300	1.830/.15	2.50	18.885
J - #24639	6.080	6063-T6	0.500	0.250	0.250	2.213/.18	2.95	20.016
K - #24684	4.850	6063-T5	0.805	0.660	0.140	1.601/.13	2.12	31.100
L - #24688	3.945	6063-T6	2.875	2.500	.0375	4.849/.40	1.45	57.344
M - #25979	2.000	6063-T5	1.681	1.451	0.230	1.698/.15	1.50	27.725
N - #24884	4.600	6063-T5	1.681	1.451	0.230	3.768/.31	1.40	60.253
P - #24939	4.900	6063-T6	1.300	1.000	0.300	2.978/.25	1.68	35.270
Q - #24964	2.079	6063-T6	0.562	0.464	0.098	0.532/.04	7.54	12.559
R - #25092	12.000	6063-T6	1.300	1.000	0.300	7.249/.60	0.85	83.852
S - #25206	8.000	6063-T5	1.375	1.000	0.375	6.553/.55	0.90	75.938
T - #25270	1.000	6063-T6	0.464	0.366	0.098	0.26148/.02	14.00	6.299
U - #25271	2.062	6063-T5	2.062	0.500	1.000	2.180/.18	6.22	24.353
V - #25363	7.984	6063-T5	0.491	0.366	0.125	2.2512/.19	1.40	46.290
W - #25380	0.601	6063-T5	0.300	0.210	0.090	0.12024/.01	16.50	2.875
X - 25445	2.425"	6063-T6	0.815	0.690	0.125	0.720/.06	5.90	12.786
Y - 25450	5.000"	6063-T5	2.500	1.25 (x2)	0.200	2.557/.21	1.70	55.456
Z - 25548	8.000"	6063-T5	3.375	3.000	0.375	13.92/1.16	0.66	156.388

HeatsinkUSA also offers cut-to-length and machining services